



---

## PLAMER BOWLUS FLUME

# STANDARD OPTIONS

---

- **STAFF GAUGE:** Available in various widths and markings including flow data
- **STILLING WELL:** Integral or remote; 6", 8", 10", or 12" ID – with or without plug.
- **BUBBLER TUBE:** Stainless Steel, ¼" ID, Integral to Flume
- **SAMPLER TUBE:** Stainless Steel, 3/8" ID, Integral to Flume
- **INLET & OUTLET END CONNECTION:** Integral or Removable
- **PIPE CONNECTION:** Neoprene Boot or ANSI Pipe Flange Connection
- **SPECIAL CHEMICAL RESISTANT FABRICATION:** pH Range of 1 – 14
- **ULTRASONIC TRANSDUCER BRACKET:** Fixed at 14" or 24" or Adjustable
- **pH SENSOR CAVITY:** Fabricated to fit most sensors
- **WING WALLS & BULK HEADS:** Custom Fabricated to meet job requirements
- **NESTING OPTIONS:** Standard or Special Designs
- **ENERGY ABSORPTION RACKS:** Fixed or Removable
- **STANDARD OR SPECIAL DEPTHS:** Including surge boxes
- **ENCLOSED FLUMES:** for odor control
- **FLUME COVERS:** Grating, Fiber Sheeting, Clear Polycarbonate
- **SPECIAL DESIGN:** will meet your special project needs